

Tipo: FLEX


Cavi flessibili L = 1000 mm.
dall'interno in nichel, isolamento
in fibra di vetro.

Tipo: TCJ

Cartuccia con termocoppia
incorporata tipo "J" cavi flessibili
L=1000 mm, isolamento in PTFE.

Tipo: HE

Cavi saldati e isolati da
boccola in ceramica H=2 mm



Tolleranze / Tolerances

Ø -0,04/-0,07mm L ±1,5% W ±10%

Ø	Lunghezza / Length	V.230 Watt	FLEX o HE	TCJ
10	40	125	100440125	-
		160	100440160	100410160
		200	100440200	100410200
		250	100440250	100410250
	50	160	100540160	-
		200	100540200	100510200
		250	100540250	100510250
		315	100540315	100510315
	60	400	100540400	100510400
		160	100640160	-
		200	100640200	100610200
		250	100640250	100610250
	80	315	100640315	100610315
		400	100640400	-
		500	100640500	-
		630	100840630	-
	100	200	100840200	-
		250	100840250	100810250
		315	100840315	100810315
		400	100840400	100810400
		500	100840500	-
		630	100840630	-
	100	250	101040250	-
		315	101040315	101010315
400		101040400	101010400	
500		101040500	101010500	
630		101040630	-	
800		101040800	-	

Ø	Lunghezza / Length	V.230 Watt	FLEX o HE	TCJ
10	130	250	101340250	-
		315	101340315	101310315
		400	101340400	101310400
		500	101340500	101310500
		630	101340630	-
		800	101340800	-
	160	315	101640315	-
		400	101640400	-
		500	101640500	101610500
		630	101640630	101610630
	200	800	101640800	-
		400	102040400	-
		500	102040500	102010500
		630	102040630	-
	250	800	102040800	102010800
		630	102540630	-
		800	102540800	-
		1000	102541000	-