

Tipo: FLEX


Cavi flessibili L = 1000 mm.
dall'interno in nichel, isolamento
in fibra di vetro.

Tipo: TCJ

Cartuccia con termocoppia
incorporata tipo "J" cavi flessibili
L=1000 mm, isolamento in PTFE.

Tipo: HE

Cavi saldati e isolati da
boccola in ceramica H=4 mm



Tolleranze / Tolerances

Ø -0,05/-0,08mm L ±1,5% W ±10%

Ø	Lunghezza / Length	V.230 Watt	FLEX o HE	TCJ
12,5	40	160	120440160	-
		200	120440200	120410200
		250	120440250	-
		315	120440315	-
	50	160	120540160	-
		200	120540200	-
		250	120540250	-
		315	120540315	120510315
	60	400	120540400	120510400
		200	120640200	-
		250	120640250	120610250
		315	120640315	120610315
	80	400	120640400	-
		500	120640500	-
		250	120840250	120810250
		315	120840315	-
	100	400	120840400	-
		500	120840500	-
		630	120840630	-
		315	121040315	-
400		121040400	121010400	
500		121040500	-	
	630	121040630	121010630	
	800	121040800	-	
	1000	121041000	-	

Ø	Lunghezza / Length	V.230 Watt	FLEX o HE	TCJ
12,5	130	400	121340400	121310400
		500	121340500	-
		630	121340630	121310630
		800	121340800	-
		1000	121341000	-
	160	500	121640500	-
		630	121640630	-
		800	121640800	121610800
		1000	121641000	-
	200	1250	121641250	-
		630	122040630	122010630
		800	122040800	-
		1000	122041000	122011000
	250	1250	122041250	-
		800	122540800	122510800
		1000	122541000	-
		1250	122541250	122511250
	300	1500	122541500	-
		1000	123041000	-
		1250	123041250	-
1500		123041500	-	
	2000	123042000	-	