


Tipo: FLEX

Cavi flessibili L = 1000 mm.
dall'interno in nichel, isolamento
in fibra di vetro.



Tipo: HE

Cavi saldati e isolati da
boccola in ceramica H=6 mm



Tolleranze / Tolerances

Ø -0,05/-0,08mm L ±1,5% W ±10%

Ø	Lunghezza / Lenght	V.230 Watt	FLEX o HE
16	50	200	160540200
		250	160540250
		315	160540315
		400	160540400
	60	200	160640200
		250	160640250
		315	160640315
		400	160640400
		500	160640500
	80	250	160840250
		315	160840315
		400	160840400
		500	160840500
		630	160840630
		800	160840800
	100	315	161040315
		400	161040400
		500	161040500
		630	161040630
		800	161040800
1000		161041000	
130	400	161340400	
	500	161340500	
	630	161340630	
	800	161340800	
	1000	161341000	
	1250	161341250	

Ø	Lunghezza / Lenght	V.230 Watt	FLEX o HE
16	160	500	161640500
		630	161640630
		800	161640800
		1000	161641000
		1250	161641250
	200	630	162040630
		800	162040800
		1000	162041000
		1250	162041250
		1500	162041500
		2000	162042000
	250	1000	162541000
		1500	162541500
		2000	162542000
	300	1000	163041000
		1250	163041250
		1500	163041500
		2000	163042000
	350	1000	163541000
1500		163541500	
2000		163542000	
400	1000	164041000	
	1250	164041250	
	1500	164041500	
	2000	164042000	