

Tipo: FLEX

Cavi flessibili L = 1000 mm.
dall'interno in nichel, isolamento
in fibra di vetro.



Tipo: HE

Cavi saldati e isolati da
boccola in ceramica H=6 mm



Tolleranze / Tolerances

Ø -0,05/-0,08mm L ±1,5% W ±10%

Ø	Lunghezza / Length	V230 Watt	FLEX o HE
5/8" (15,87mm)	2" (50,8mm)	200	170540200
		250	170540250
		315	170540315
		400	170540400
	2" ½ (63,5mm)	200	170640200
		250	170640250
		315	170640315
		400	170640400
		500	170640500
	3" (76,2mm)	250	170840250
		315	170840315
		400	170840400
		500	170840500
		630	170840630
		800	170840800
	4" (101,6mm)	315	171040315
		400	171040400
		500	171040500
		630	171040630
		800	171040800
		1000	171041000
	5" (127mm)	400	171340400
		500	171340500
		630	171340630
800		171340800	
1000		171341000	
1250		171341250	
6" (152,4mm)	500	171540500	
	630	171540630	
	800	171540800	
	1000	171541000	
	1500	171541500	

Ø	Lunghezza / Length	V230 Watt	FLEX o HE
5/8" (15,87mm)	7" (177,8mm)	500	171840500
		800	171840800
		1000	171841000
		1500	171841500
	8" (201,6mm)	630	172040630
		800	172040800
		1000	172041000
		1250	172041250
		1500	172041500
		2000	172042000
	10" (254mm)	1000	172541000
		1500	172541500
		2000	172542000
		1000	173141000
	12" (304,8mm)	1250	173141250
		1500	173141500
		2000	173142000
		1000	173441000
	14" (355,6mm)	1500	173441500
		2000	173442000
		1000	173641000
		1500	173641500
	16" (406,4mm)	2000	173642000
		2500	173642500